

# Increase Your Productivity

A variety of accessories are available to help maximize safe productivity while operating Genie® equipment. It pays to understand what's available so you can set yourself apart. In fact, you count on a selection of practical, adaptable accessories because they are critical – sometimes required – on certain jobsites. Consider what Genie has to offer.

## Genie® Material Lift Accessories

We have a range of interchangeable load handling attachments to cater for a large variety of requirements to ensure that your Genie SLA is equipped correctly for the job in hand.



### Fork Extensions

Insert onto standard forks for an additional 25 in (64 cm) of length. Dimensions 640 x 50 x 80mm. weight 2kg

PART NO.	AVAILABLE ON
58158GT	All SLA, SLC and ST™



### Pipe Cradle

For use with standard or adjustable forks. For lifting round pipes and odd shaped items. No tools required to install or remove. Dimensions 700 x 620 x 150mm Weight 4.5 kg

PART NO.	AVAILABLE ON
80597GT	All SLA



### Boom Option - SLA™ & SLC™

Transforms your lift into a mobile, vertical crane or hoist to position tooling fixtures, circuit breakers, engines and more. Dimensions 1070 x 40 x 165mm. Weight 18 kg

PART NO.	AVAILABLE ON
32567-SGT	All SLA and SLC

= Factory Installed = Aftermarket

# Genie® Superlift Advantage® SLA™ -5, SLA-10, SLA-15, SLA-20 & SLA-25

## SKU: Standard Model

- SLA-5, Standard base\*
- **SLA50001A00002**: SLA-5, Straddle base
- **SLA10001A00001**: SLA-10, Standard base
- **SLA10001A00002**: SLA-10, Straddle base

\* Build to Order

## SKU: Standard Model

- **SLA15001A00001**: SLA-15, Standard base
- SLA-15, Straddle base\*
- **SLA20001A00001**: SLA-20, Standard base, Stabilizer set
- **SLA25001A00001**: SLA-25, Standard base, Stabilizer set

Option availability		S	S+	BtO
Chassis	Rear transport wheel assembly			○
	Heavy-duty design	✓	✓	✓
	Portable compact design for easy transport and storage	✓	✓	✓
	Quick setup requires no tools	✓	✓	✓
	Stabilizer set (standard on SLA-20, SLA-25, not on Straddle base)			○
Mast	Mast brake			○
	One-speed manual winch, locks load in place	✓	✓	✓
	Patented telescoping mast system	✓	✓	✓
	Strong and lightweight aluminum telescoping mast	✓	✓	✓
	Transport carriage lock	✓	✓	✓
Two speed winch (SLA-15, SLA-20, SLA-25 only)			○	
Wheels	4in/10cm non-marking front casters	✓	✓	✓
	5in/12cm rear casters with side brakes	✓	✓	✓
Attachments	Durable standard steel forks	✓	✓	✓
	Adjustable width forks		○	○
	Boom		○	○
	Flat forks (SLA-5, SLA-10, SLA-15)		○	○
	Fork extensions (use on Standard or Adjustable forks)		○	○
Load platform		○	○	

- S Standard
- S+ Standard +
- BtO Build to Order
- ✓ Standard Features
- Options



Quick Setup



Truck Portable



Max Lift Capacity  
1000lb/454kg



Genie Genuine Accessories<sup>(1)</sup>

(1) More accessories available from Genie Genuine Parts.

Product specifications are subject to change without notice or obligation. Photographs and/or drawings herein are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on proper equipment use. Failure to follow instructions in the Operator's Manual may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Terex, Genie, Xtra Capacity, Lift Power, Lift Guard, Lift Tools, Lift Connect and Tech Pro Link are registered trademarks of Terex Corporation or its subsidiaries.

11/22

**Genie**®

© 2022 Terex Corporation

**QUALITY** BY DESIGN