FloorCare

TBL4045 Fast Charge, Long Life, Flexible Power



TBL4045

Powered by NX1K, with 40L capacity and 450mm scrub width, user-friendly controls and on-board charging system. The 4045 is the ultimate in mid-sized scrubber versatility and performance.

POWERFUL Cleaning Results

NX1K Battery Range powers commercial grade TwinFlo vacuum and brush motor for unrivaled cleaning performance in the most demanding environments.

CLEAN, DRY & SAFE Floors in Minutes Consistent, quick and high-quality cleaning results, wherever they're needed.

FAST & FLEXIBLE Charging Latest lithium phosphate technology provides fast charging with complete flexibility, with no impact on battery health.

USER FRIENDLY Features Incorporating user-friendly, colour-coded controls for ease of use.

STAY CLEANING for Longer Huge 40L capacity, 100rpm brush speed and 450mm brush width provides powerful cleaning results.

MT Assist

With the Nu-Assist App on hand, you and your team have 24/7 access to multilingual training, troubleshooting and maintenance content from any device, increasing cleaning productivity across the board.

Next Generation Lithium Power

4x Longer Lasting than Lead Batteries Advanced & Safe Lithium **Phosphate Technology Flexible Charging** 4000 Charge Cycles Extended Long-Life Powert



Accessories and Replacement Parts

A comprehensive range of accessories and replacement parts are available to achieve professional results, whatever the challenge.

Specifications

Model	Batteries	Power	Runtime	Recharge	Capacity	Deck	Brush	Pad	Dimensions
TBL4045	x1	720W	1hr 40mins	2hr 30mins	40L	450mm	450mm	400mm	470x890x1
	x2	720W	3hrs 10mins	5hrs	40L	450mm	450mm	400mm	470x890x1

*Any comparisons used are based on typical usage scenarios, results may differ. Performance comparisons use equivalent GelTec models.

umatic

[†]Standard battery warranty is 5 years, with up to 8 years battery warranty available subject to terms and market agreement. Please contact Numatic for more information.

(WxI xH) 100mm 100mm

> MADE IN TH UNITED KINGDOM

numatic.com

©Numatic International Limited 2023. Specification subject to change without prior no