


SL45NE

Dingli 45ft
JCPT1612AC
All Electric
Scissor Lift



We want you to have the best experience possible with Dromad Hire that's why we offer a range of products and services to help you complete your tasks, safely, conveniently, and cost effectively.

This narrow scissor lift provides a massive working height of 16m. At only 1.25m wide it is easy to manoeuvre in small confined spaces and is ideal for any warehousing maintenance work or construction.

The all-electric drive provides fast and controlled movements along with zero noise or emissions and an industry-leading run time per battery charge.

Key Features

- Impressive 16m Working Height
- Drivable At Full Height
- Non-Marking Tyres
- Only 1.25m Wide
- Zero Noise Or Fumes For Unrestricted Working Hours
- Foldable guard rails
- Onboard fault diagnostics system
- One way platform extension deck



Technical Specification

Max. Working Height A	15.70m	51ft 6in
Max. Platform Height B	13.70m	44ft 11in
Overall Length C	2.84m	9ft 4in
Overall Width D	1.25m	4ft 1in
Overall Height(Rails Up) E	2.62m	8ft 7in
Overall Height(Rails Down) F	2.09m	6ft 10in
Platform Size(Length×Width)	2.64m×1.12m	8ft 8in×3ft 8in
Platform Extension Size G	0.90m	2ft 11in
Ground Clearance(Stowed/Raised)	0.10m/0.019m	4in/1in
Wheelbase H	2.22m	7ft 3in
Turning Radius(Inside/Outside)	0m/2.65m	0in/8ft 8in
Tyres	φ381×127mm	φ381×127mm
S.W.L	250kg	551lb
S.W.L On Extension	113kg	249lb
Max. Occupants	2	2
Gradeability	25%	25%
Travel Speed(Stowed)	5km/h	5km/h
Travel Speed(Raised)	0.8km/h	0.8km/h
Max. Working Slope	1.5°/3°	1.5°/3°
Up/Down Speed	70/67sec	70/67sec
Overall Weight(Lead-acid Battery)	3360kg	7407lb
Overall Weight(Lithium Battery)	3270kg	7209lb
Hydraulic Tank	20L	20L
Battery	4×12V/240Ah	4×12V/240Ah
Charger	24V/30A	24V/30A
Driving Motor	2×24VAC/0.87kW	2×24VAC/0.87kW
Lifting Motor	24VAC/3.5kW	24VAC/3.5kW

* The platform height plus 2m (7ft in British standard) is the working height.
Standards Compliance

