

We want you to have the best experience possible with Dromad Hire that's why we offer a range of products and services to help you complete your tasks, safely, conveniently, and cost effectively.

This robust, highly capable micro scissor lift boasts all the specifications of a larger traditional scissor lift without the added weight and bulk. It is powered by advanced lithium batteries providing unrivalled run time on a single charge. At only 0.76m wide and under 1.85m high, it will fit through a standard door without folding the rails. This latest machine from Snorkel is the contractor's choice, and it is ideal for any factory maintenance application or order picking.

# **Key Features**

- Lithium battery powered lasts up to four times longer than traditional batteries
- No folding rails
- Fits through a standard door without folding rails
- Lightweight ( 815kg )
- Largest wheels / non-marking tyres in class
- Two-man load capacity ( 272kg )
- No hydraulic hoses
- Low step-in platform height



# Snorkel 3013 Micro Lithium Scissor Lift

R

**SL13** 

# **Snorkel 3013 Technical Specification**

DIMENSIONS	
Max. Working Height	19 ft (5.79m)
Max. Platform Height ( <b>A</b> )	13 ft (3.96m)
Platform Size (Stowed)	29.5 in x 52 in (0.74m x 1.32m)
Platform Size (Extended)	29.5 in x 76 in (0.74m x 1.93m)
Deck Extension Length	24 in (0.6m)
Overall Length ( <b>C</b> )	56.75 in (1.44m)
Overall Width ( <b>D</b> )	30 in (0.76m)
Stowed Height ( <b>B</b> )	73 in (1.85m)
Ground Clearance (Stowed)	2.63 in (0.06m)

PERFORMANCE	
Platform Capacity (SWL)	600 lbs (272.1kg)
Max. Wind Speed	28 mph (45kph)
Max. Drive Height	13 ft (4.33m)
Max. Drive Speed (Stowed)	2.5 mph (4.0kph)
Max. Drive Speed (Elevated)	0.5 mph (0.8kph)
Raise/Lower Time	30/20 sec
Gradeability	25%
Max. Operation Slope (side-to-side)	1.5 degrees
Max. Operation Slope (front-to-back)	2 degrees
Inside Turning Radius	5 in (0.12m)
Outside Turning Radius	58 in (1.47m)
Tires	12.7 in (0.32m)
Controls	Proportional
Drive System	Dual DC Motors
Parking Brake	2-wheel, spring applied

POWER	
Power Source	24V 60Ah Lithium Battery
Charger	20A

5 in (0.12m

**TURNING RADIUS** 


outside 58 in (1.47m)

General

Plant & Tool Hire

Weight


1,796 lbs (815kg)



### STANDARD FEATURES

- 100% Operation 2 person indoor, 1 person outdoor
- Lithium battery operated scissor lift
- No hydraulic hoses
- Fits standard doorway *without* folding rails
- Roll-out-deck with dual locks
- Non-marking tires—largest wheels/tires in class
- Heavy-duty spindles/steering
- Heavy-duty fixed control box
- Descent and all-motion alarms
- Proportional control, all functions
- Platform overload protection
- 110 V (15 amp) power to platform
- On-board diagnostics, hour meter, battery meter
- Automatic integrated battery charger
- Manual safety lowering system
- Flashing amber strobe
- Forklift pockets, crane lifting points
- Lanyard attachment points
- Swing-out service trays
- 2-year parts & labor warranty
- 5-year lithium battery & structural warranty

## Available to Hire or Buy



info@dromadhire.com

# dromadhire.com

Dublin+353 1 908 1005Dundalk+353 42 933 9500

 $\bowtie$