

SITE DUMPERS



WORKS FOR YOU.™

SPECIFICATIONS

PERFORMANCE

	TA1EH	TA2H	TA2SH	TA2SEH	TA3	TA3S
Payload (Kg)	1000	2000	2000	2000	3000	3000
Unladen Weight (Kg)	1310	1964	2082	2166	2280	2330
Tipping Type	Forward Tip – High Discharge	Forward Tip	Swivel Tip	Swivel Tip – High Discharge	Forward Tip	Swivel Tip
Skip Capacity – Water (litres)	320	750	750	750	1250	1000
Skip Capacity – Struck (litres)	450	1000	1000	1000	1600	1520
Skip Capacity – Heaped (litres)	540	1200	1200	1200	1950	1880
Engine	Kubota D905		Kubota D1703M		Kubota V2203M	
– Number of Cylinders	3		3		4	
– Gross Power – kW (hp)	15.5kW (20.8)		24.5 (32.6)		32.4 (43.5)	
– Displacement (cc)	898		1647		2197	
– Maximum Torque (Nm)	56Nm		105		145	
– Aspiration	Naturally Aspirated		Naturally Aspirated		Naturally Aspirated	
– Emission Compliance	EU Stage 3A		EU Stage 3A		EU Stage 3A	

TRANSMISSION/DRIVE

Transmission Type	Hydrostatic Pump (Poclair Twinlock) to 4 Hydraulic Wheel Motors	Hydrostatic Motor via Transfer Box to Front & Rear Axles	Manual Gearbox via Transfer Box to Front & Rear Axles
Tyre Size	255 / 75 x 15.2 x 8 ply (option 7.0 x 12 narrow tyre)	10.0 / 75 x 15.3 (10 ply)	295/80 x 15.3 x 10 ply
Drive	Hydrostatic 1/1	2 / 2 (High & Low Range – Forward & Reverse) Hydrostatic – Permanent 4WD	Manual – 3 Forward / 1 Reverse
Maximum Travel Speed – mph (kph)	7 (11)	10.0 (16.0)	11.8 (19.0)
Gradeability (Maximum Slope Gradient)	20% (1 in 5)	19.5% (1 in 5)	25% (1 in 4)

CAPACITIES

Fuel Tank Capacity (litres)	35	23	37
Hydraulic Tank Capacity (litres)	25	25	37

ENVIRONMENTAL

Noise Emission (to ISO 4871) – Sound Pressure (LpAd)	83 dB	86.1 dB	84 dB
Sound Power Level (LWAd)	101 dB	101 dB	101 dB
Noise Compliance	Noise – Equipment Used Outdoors Directive 2000/14/EC		
Vibration – Hand Arm (as defined in EN474-1 all operations)	<2.5 m/s ²		
Vibration – Whole Body (as defined in ISO/TR 25398 – Work Cycle)	0.529 rms (0.264 m/s ² Uncertainty)		

HYDRAULIC SYSTEM

Pump Type	Gear			
Flow Rate	29 l/min	21 l/min	30l/min	
Operating Pressure	152 bar	210 bar	172 bar	210 bar
Steering System	Orbitrol hydrostatic steering unit powering central hydraulic steering ram	Orbitrol hydrostatic steering unit powering central hydraulic steering ram		

TA3H	TA3SH	TA3.5SH	TA6	TAGS	TA9	TA10
3000	3000	3500	6000	6000	9000	10000
2290	2340	2340	4350	4410	4590	4635

Forward Tip	Swivel Tip	Swivel Tip	Forward Tip	Swivel Tip	Forward Tip	Forward Tip
1250	1000	1000	1950	1850	2064	2446
1600	1520	1520	2750	2740	3899	4128
1950	1880	1880	3780	3530	4587	5046
Kubota V2203M		JCB EcoMax		JCB EcoMax		
4		4		4		
32.4 (43.5)		55 (74)		55 (74)		
2197		4400		4400		
147		400		400		
Naturally Aspirated EU Stage 3A		Turbocharged		Turbocharged		
				EU Stage IIIB / Tier 4 Final		

Hydrostatic Motor via Transfer Box to Front & Rear Axles	Powershuttle via Transfer Box to Front & Rear Axles	Powershuttle via Transfer Box to Front & Rear Axles - Powershift as option	Powershift via Transfer Box to Front & Rear Axles
--	---	--	---

295/80 x 15.3 x 10 ply

405-70-20 14PR

500-60-22.5 16PR

2 / 2 (High & Low Range - Forward & Reverse) Hydrostatic - Permanent 4WD	4 / 4 Forward and Reverse - Permanent 4WD	
11.8 (19.0)	16.3 (26.2)	15.4 (24.83)
25% (1 in 4)	25% (1 in 4)	20% (1 in 5)

37	65	65
37	50	50

84 dB	81 dB	81 dB
101 dB	101 dB	101 dB

Noise - Equipment Used Outdoors
Directive 2000/14/EC

<2.5 m/s²

0.529 rms (0.264 m/s² Uncertainty)

Gear		Gear		Gear	
30 l/min		48.3 l/min		60 l/min	
172 bar	210 bar	210 bar	172 bar	172 bar	172 bar
					210 bar

Orbitrol hydrostatic steering unit powering central hydraulic steering ram

BRAKING SYSTEM

	TA1EH	TA2H	TA2SH	TA2SEH	TA3	TA3S
Working Brake	Hydrostatic Dynamic Braking on Rear Wheel Motors		Multi-Plate In-Board Oil Immersed Discs on Front Axle			
Parking Brake	Hydrostatic Dynamic Braking on Rear Wheel Motors		Over Centre Handbrake – Oil Immersed Discs on Front Axle			

ELECTRICAL SYSTEM

Voltage	12V			12V		
Battery	74Ah			74Ah		
Alternator	30A			55A		

DIMENSIONS

Total Length (mm)	2980	3570	3550	3550	3725	3952
Total Width (Max) (mm)	998* / 1120	1492	1492	1492	1957	1846
Wheelbase (mm)	1440	1900	1900	1900	1939	1939
Ground Clearance (mm)	241	184	184	184	279	279
Height to Front Lip of Skip (untipped) (mm)	1167	1323	1360	1522	1371	1467
Height to Front Lip of Skip (tipped) (mm)	1620 (raised)	916	983	1142 (lowered) / 1640 (raised)	208	762
Turning Radius to Outside of Skip (mm)	2295	3680	3680	3680	4711	4553
Steering Angle	+/- 45°		+/- 30.6°			+/- 30°
Oscillation	+/- 14°			+/- 10.5°		
Height to Top of ROPS (raised with beacon) (mm)	2832			2920		

* When fitted with narrow tyres

STANDARD EQUIPMENT AND OPTIONS

Folding ROPS Frame	Standard			Standard		
Reversing Alarm	Standard			Standard		
Flashing Beacon	Standard			Standard		
Towing/Recovery Bracket	-			Standard		
Leg Guard	Option			Standard		
Hour Metre	Standard			Standard		
Road Lights (RTA) including Front Light Guards	Option			Option		
Rear View Mirror	-			Option (standard in some markets - check with your local Terex dealer)		
CESAR Datatag Security	Option			Option		
Fan Guard	-			Option (standard in some markets - check with your local Terex Dealer)		
Spare Wheel	Option			Option		
Special Paint	Option			Option (standard in some markets - check with your local Terex Dealer)		
Seat Belt (High Visibility Orange)	Standard			Standard		
Seat (adjustable fore/aft, operator weight and back angle)	Standard			Standard		
Heavy Duty Articulation Lock	Standard			Standard		
Narrow Tyres (7.00 x 12)	Option			-		
Wide Tyres (255 / 75 x 15.2 8ply)	Standard			-		
High Visibility Safety Decals for Steps & Handrails	Option			Option		
German / Swiss Road Homologation Kit	Option	Option	Option	Option		-
Water in Fuel Monitoring	-			-		
Coolant Level Monitoring	-			-		

TA3H	TA3SH	TA3.5SH	TA6	TAGS	TA9	TA10
Multi-Plate In-Board Oil Immersed Discs on Front Axle			Foot Brake – Oil immersed discs on front/rear			
Over Centre Handbrake – Oil Immersed Discs on Front Axle			Over Centre parking brake – dry disc in gearbox			
12V			12V			
74Ah			100Ah			
55A			95A			

3725	3952	3952	4405	4539	4484	4530
1957	1846	1846	2300	2207	2500	2550
1939	1939	1939	2450	2450	2450	2450
279	279	279	385	385	410	410
1371	1467	1467	1672	1732	1722	1760
208	762	762	504	1258	430	440
4711	4553	4553	5863	5726	5994	6011
+/- 30°			+/- 30°			
+/- 10.5°			+/- 10°			
2920			3203	3203	3635	3635

Standard			Standard			
Standard			Standard			
Standard			Standard			
Standard			Standard			
Standard			Option			
Standard			Standard			
Option			Option			
Option (standard in some markets – check with your local Terex Dealer)			Option (standard in some markets – check with your local Terex Dealer)			
Option			Option			
Option (standard in some markets – check with your local Terex Dealer)			Option			
Option			Option			
Option (standard in some markets – check with your local Terex Dealer)			Option			
Standard			Standard			
Standard			Standard			
Standard			Standard			
-			-			
-			-			
Option			Option			
Option	Option	Option	-	Option	-	-
-			Standard			
-			-	-	Standard	Standard