



OBS 18DC Orbital Sander

Wood Floor Sanding

- 1 The totally enclosed, fan cooled motor, eliminates overheating and the need for motor cleaning.
- 2 Heavy duty cast aluminum main frame and pad driver plate for added strength.
- 3 Independent dust pickup fan for effective dust containment.
- 4 Dust pipe allows for easy attachment of 3.8 cm or 5.1 cm vacuum hoses for improved dust containment.
- 5 Bristle dust skirt to aid in dust containment (not shown).
- 6 Transparent molded plug has an internal light that serves as a power indicator.



PRODUCT DESCRIPTION

The random-orbital sanding action of the OBS-18DC removes the scratch patterns left by drum or rotary sanders, leaving a smooth, flat floor ready for refinishing. At 3,000 orbits per minute, the OBS-18DC sands faster than any other orbital sander available. With torque-less operation for enhanced operator comfort, the OBS-18DC is perfect for interim "screen and recoat" and fine finish sanding jobs.

RECOMMENDED PRODUCTS



AVAC dust containment systems are the perfect mix of power and portability. At 45 and 98 liter capacities, both models are easy to transport and are available with optional H.E.P.A. filters.

TECHNICAL DATA

Electrical Motor 0.75 kW, Universal, totally enclosed, 230V, 50 Hz

Sanding Path 45.7 cm

Power Cord 12.2 m gray, non-marking rubber

Sanding Pad Size 30.5 cm x 45.7 cm

Abrasive Speed 3,000 orbits per minute

Sound Level 74 dBA

Wheels (2) 7.6 cm

Size (L x W x H) 46 cm x 51 cm x 114 cm

Machine Weight 56.7 kg

Shipping Weight 66 kg

Warranty Machine: Parts & Labor - 1 yr*
*Excludes consumable wear items

*Specifications are subject to change without notice.

Hire Today...

Dublin 01 908 1005

Dundalk 042 933 9500

dromadhire.com