

STANDARD PRODUCT

KRS-40-SLD



HILMAN ROLLERS Deluxe FT SERIES KIT featuring (4) 10-SLD Rollers, (4) P-1 Preload Pads and (2) KDH48F Steering Handles in an all Steel Carrying Case.

Product Specifications

Top Style: Swivel-Locking Diamond

Capacity Rating: 40 metric ton (entire set)
10 metric ton (each roller)

Weight: 219 lb. (99 kg.)

Individual Roller Specifications

Height: 5" (127 mm)

Width: 5 3/4" (146 mm)

Length: 10 1/2" (267 mm)

Roller Features:

- Swivel-locking top
- Hard steel cast diamond swivel top with up to 80 gripping teeth
- Chrome steel ball bearing swivel race
- Chains made of hardened and concentrically ground alloy rolls
- Roller chain made of plated steel links.
- Serialized rollers carry a **full five-year warranty**

Roller Benefits:

- Offers maximum positioning ability
- Provides ample gripping strength
- To ease turning
- Provides even load bearing across footprint
- For added corrosion resistance
- Made to last and to be worry free

Accessories

Steering Handles: Each KRS-40-SLD contains (2) two KDH48F Steering Handles for roller positioning. Each 48" (1219 mm) handle is in "knock down" form joined by a heavy coupling, weighs 12 lb. (5 kg.) and feature tough safety rubber grips.

Carrying Case: The KRS-40-SLD is fully contained in one Deluxe Kit Box made of heavy steel construction. Case features lockable, double hasps and two handles for handling ease.

Preload Pads: Each KRS-40-SLD contains (4) four P-1 pads which are 1/2 inch (13 mm) thick. The Pads are made of 80 durometer neoprene to ensure a non-slip surface between roller and load.